



SPECIFICATIONS

ENGINE: LIQUID-COOLED V-TWIN (60 DEGREES)

Engine	DOHC, 4-valves per cylinder, semi-dry sump
Transmission	6-speed, constant mesh / foot shift
Battery	12 volts, 13 amp/hour, 245 CCA
Bore x Stroke	99 mm x 74 mm
Charging System	35 amp max output
Clutch	Wet, multi-plate
Compression Ratio	10.7:1
Cooling System	Liquid
Displacement	1133 cc
Exhaust	Split dual exhaust with cross-over
Final Drive	Belt drive, 141 tooth
Fuel & Capacity	91 octane recommended, 12.5 ltr
Fuel System	Electronic fuel injection, closed loop / 60 mm bore
Oil	SAE 15W60, 4.3 ltr
Primary Drive	Gear drive wet clutch
Horsepower	70 kW at 8100 rpm
Peak Torque	97 Nm at 5600 rpm

SUSPENSION

Front Suspension	Telescopic fork, 41 mm diameter, 120 mm travel
Rear Suspension	Dual shocks, 51 mm travel, adjustable

CHASSIS

Weight (As Shipped)	238 kg
Ground Clearance	129 mm
GVWR	449 kg
Length	2274 mm
Rake/Trail	29° / 120 mm
Seat Height	649 mm
Wheelbase	1576 mm

BRAKES

Brake System Type	Individual front and rear control, ABS
Front Braking System	Single 298 mm floating rotor with 2-piston calipers
Rear Braking System	Single 298 mm floating rotor with 1-piston caliper

WHEELS & TIRES

Front Tire	Metzeler® Cruisetec® 130/60B19 61H
Front Wheel	Cast Black 19" x 3.5"
Rear Tire	Metzeler® Cruisetec® 150/80R-16
Rear Wheel	Cast Black 16" x 3.5"

COLORS

Black Smoke
Storm Blue
Sagebrush Smoke
Stealth Gray
Black Azure Crystal
Copper Metallic

For pricing and availability in your region, please contact your local Indian Motorcycle press contact. Images may show North American models and may have accessories fitted. International models may vary.