



SPECIFICATIONS

ENGINE: THUNDERSTROKE 116

Engine Type	49° V-Twin
Transmission	6-speed/constant mesh/foot shift
Battery	12 volts / 18 amp/hour, 310 CCA
Bore x Stroke	4.063 in x 4.449 in (103.2 mm x 113 mm)
Charging System	42 amp max output
Clutch	Wet, multi-plate
Compression Ratio	11.0 : 1
Cooling System	Air
Displacement	116 cu in / 1890 cc
Exhaust	Split dual exhaust with crossover
Final Drive	Belt drive, 152 tooth
Fuel Capacity	5.5 gal (20.8 ltr)
Fuel System	Electronic fuel injection, closed loop/54 mm bore
Oil Capacity	6 qts (5.68 ltr)
Primary Drive	Gear drive wet clutch
Torque	126 ft-lbs at 2900 rpm (168 Nm at 2900 rpm)

SUSPENSION

Front Suspension	Telescopic fork, 46 mm diameter, 119 mm travel
Rear Suspension	Single shock 114 mm travel, air adjustable

CHASSIS

Weight (As Shipped)	344 kg
Ground Clearance	130 mm
GVWR	628 kg
Length	2522 mm
Rake/Trail	25° / 133 mm
Seat Height	665 mm
Wheelbase	1701 mm

BRAKES

Brake System Type	Individual front and rear control, ABS
Front Braking System	Dual 300 mm floating rotor with 4-piston calipers
Rear Braking System	Single 300 mm floating rotor with 2-piston caliper

WHEELS & TIRES

Front Tire	Metzeler® Cruisetec® 130/60B19 66H
Front Wheel	10-Spoke Contrast Cut 19" x 3.5" with tire pressure monitoring
Rear Tire	Metzeler® Cruisetec® 180/60R16 80H
Rear Wheel	10-Spoke Contrast Cut 16" x 5.0" with tire pressure monitoring

COLORS

Black Smoke
Quartz Gray

For pricing and availability in your region, please contact your local Indian Motorcycle press contact. Images may show North American models and may have accessories fitted. International models may vary.