



SPECIFICATIONS

ENGINE: THUNDERSTROKE 116

Engine Type	Air-Cooled 49° V-twin with Rear Cylinder Deactivation
Displacement	1890 cc
Bore x Stroke	103.2mm x 113mm
Compression Ratio	11.0 : 1
Lubrication System	Semi-Dry Sump
Fuel System	Closed loop/54 mm bore single throttle body
Fuel Capacity	15.1 ltr not including reserve
Exhaust	Dual exhaust with crossover
Peak Torque	162 Nm at 2900 rpm
Primary Drive	Gear drive wet clutch
Transmission	6-speed/constant mesh
Clutch	Wet, multi-plate
Final Drive	Belt drive, 146 tooth
Battery	12 volts / 18 amp/hour, 310 CCA with quick connect charge port

SUSPENSION

Front Suspension	Telescopic fork, 46 mm diameter, 132 mm travel
Rear Suspension	Dual gas-charged monotube shocks with adjustable preload, 75mm travel

CHASSIS

Chassis Type	Steel tube weldment with cast aluminum rear sub-frame
Wheelbase	1626 mm
Rake/Trail	29° / 132 mm
Lean Angle (soft)	28.5°
Seat Height	665 mm
Weight (As Shipped)	324 kg
Ground Clearance	125 mm
GVWR	522 kg
Length	2286 mm
Storage Capacity	36.6 ltr

BRAKES

Brake System Type	Individual front and rear control, ABS
Front Braking System	Single 4 piston caliper / 300mm Semi-Floating Rotor
Rear Braking System	Single 2 piston caliper / 300mm Floating Rotor

WHEELS & TIRES

Front Tire	Pirelli® Night Dragon 130/90B16 67H
Front Wheel	Black Wire 16" x 3"
Rear Tire	Pirelli® Night Dragon 180/65 B16 81H
Rear Wheel	Black Wire 16" x 5"

STANDARD FEATURES

Lighting	LED Headlights, LED stop/turn/taillights
Gauges	101 mm Touchscreen Powered By RIDE COMMAND with Navigation and Bluetooth®
Controls	Cruise Control, 3 Selectable Ride Modes, Keyless Ignition

COLORS

Black Metallic
Silver Quartz Metallic
Stryker Red Metallic

For pricing and availability in your region, please contact your local Indian Motorcycle press contact.
Images may show North American models and may have accessories fitted.
International models may vary.
Navigation may not be available in all countries.